

QuantaMesh 3000 Series BMS T3048-LY2

A Powerful Top-of-Rack Switch for Cloud Datacenters



Overview

Datacenter networks are facing a major paradigm shift toward the disaggregation of software and hardware. This move, combined with the benefits of software-defined networking (SDN) allows network administrators respond quickly to changing business requirements at a lower capital cost as well as reducing the network operations complexity.

QuantaMesh BMS products offer higher performance, increased availability, low latency and better serviceability. QuantaMesh T3048-LY2 supports 48 SFP+ (1/10GbE speed) and 4 QSFP+ (10/40GbE speed) ports in a compact 1U size. By leveraging merchant silicon chips, T3048-LY2 is a high performance high density Ethernet switch with an affordable price for the deployment of data center infrastructure. With ONIE (Open Network Installation Environment) pre-loaded on QuantaMesh BMS switches, it provides the flexibility and allows choice of network operating system supported by ONIE installer. This provides agile installation process and faster response for the changing business demand.

QCT LLC.

47709 Fremont Boulevard, Fremont CA 94538

Main: +1-510-270-6111 Fax: +1-510-270-6161 Support: +1-510-270-6216

Toll Free: 1-855-QCT-MUST

E-mail: sales@QuantaQCT.com For more information, please visit

http://www.QuantaQCT.com

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

Quanta and the Quanta logo are registered trademarks of Quanta Computer Inc. All trademarks and logos are the properties of their representative holders. Copyright ©2013 Quanta Computer Inc. All rights reserved.

Simplicity -----

48 SFP+ ports support 1/10GbE

4 QSFP+ ports support 10/40GbE

1 RJ-45 out-of-band management port (10/100/1000M)

1 RJ-45 console port

1+1 hot-swappable power supply

High Switching Performance -----

Switching capacity: 1.28Tbps Forwarding rate: 960Mpps 1.2 microseconds latency Memory: 2GB DDR3

Flash: 64MB MAC: 128K

Packet buffer: 9MB Jumbo frame: 12K Storage: 2GB MicroSD

Mechanical -----

Dimension (HxWxD): 42.8x435x393.7 mm

Weight: 7.7kg (NET)

Operation Environment -----

Operating temperature: 0~45°C

Operating humidity: 90% maximum relative humidity

Safety -----

UL, cUL, CB, BSMI, CCC

EMC -----

CE, FCC, VCCI, MSIP, BSMI, CCC

Environmental -----

Reduction of Hazardous Substances (RoHS) 6

Order information -----

T3048-LY2 (1LY2BZZ000R) (Front to Back)
T3048-LY2 (1LY2BZZ000S) (Back to Front)