

QuantaMesh T5032-LY6

A Powerful
Spine/Leaf Switch for
Datacenter and
Cloud Computing



The QuantaMesh T5032-LY6 is a high performance and low latency layer 2/3/4 Ethernet switch with 32 40GbE QSFP+ ports in a 1U form factor. Each 40G QSFP+ port can be independently configured as 40GbE or 4 10GbE. The T5032-LY6 supports up to 24 40G QSFP+ ports splitting into 4 10G SFP+ ports to perform 96 10G and 8 40G ports configuration. Built for Infrastructure-as-a-service (IaaS) datacenter deployment, high performance computing clusters, and financial applications, the QuantaMesh T5032-LY6 - with its very high port density and high performance as well as ultra-low latency characteristic - is ideal for demanding workloads and provides optimal TCO.

Automation

With the rapid adoption of cloud computing and the proliferation of big data and parallel calculations, the need for datacenter network devices is growing exponentially, making network automation a critical factor. Supporting auto installation, QuantaMesh T5032-LY6 facilitates for easy deployment and build-up of mass datacenter IaaS.

Virtualization

Network virtualization is becoming an important topic of datacenters. QuantaMesh T5032-LY6 offers a hardware-based VXLAN to support virtual machine mobility. Not limited by 4K VLANs, VXLAN enables network scale-out across L3 subnets and can support up to 16.7M possible virtual networks.

High Availability

The QuantaMesh T5032-LY6 is designed for high availability from both hardware and software perspectives. The key features include:

- 1+1 hot-swappable power supplies
- N+1 hot-swappable fans
- Out-of-band management support
- Up to 48 paths ECMP routing for load balancing and redundancy
- Multi-chassis Link Aggregation (MLAG)

- Ultra-low Latency
- MLAG, OSPF, BGP4, & ECMP
- VXLAN
- Network Automation

About QCT

Quanta Cloud Technology (QCT) is a global datacenter solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation datacenter design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined datacenter solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.

Found at: www.QCT.io/wheretobuy

United States

QCT LLC., Silicon Valley office
1010 Rincon Circle, San Jose, CA 95131
TOLL-FREE: 1-855-QCT-MUST
TEL: +1-510-270-6111
FAX: +1-510-270-6161
Support: +1-510-270-6216

China

云达科技, 北京办公室
(Quanta Cloud Technology)
北京市朝阳区东三环中路1号
环球金融中心东楼1508室
TEL: +86-10-5920-7600
FAX: +86-10-5981-7958

云达科技, 杭州办公室

(Quanta Cloud Technology)
浙江省杭州市西湖区古墩路
浙商财富中心4号楼303室
TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社
日本国東京都港区芝大門二丁目五番八号
牧田ビル3階
TEL: +81-3-5777-0818
FAX: +81-3-5777-0819

Taiwan

雲達科技 (Quanta Cloud Technology)
桃園市龜山區文化二路211號1樓
TEL: +886-3-286-0707
FAX: +886-3-327-0001

Germany

Quanta Cloud Technology Germany GmbH
Hamborner Str. 55, 40472 Düsseldorf
TEL: +49-2405-4083-1300

Other regions

Quanta Cloud Technology
No. 211 Wenhua 2nd Rd., Guishan Dist.,
Taoyuan City 33377, Taiwan
TEL: +886-3-327-2345
FAX: +886-3-397-4770

QCT authorized partner

QuantaMesh T5032-LY6

Physical ports

- **Port configuration:** 32 QSFP+ ports
- **Management Port:** Out-of-band management port (RJ-45, 10/100/1000Base-T)
- **Console Port:** 1 (RJ-45)
- **USB:** 1 (v2.0)

Performance

- **Switching capacity:** 2.56Tbps
- **Maximum forwarding rate:** 1904Mpps
- **Latency:** <600ns
- **MAC:** Unified Forwarding Table to dynamically allocate the L2/L3 tables

CPU Board

- **CPU:** Freescale P2020
- **Memory:** 2GB DDR3/ECC
- **Flash:** 128MB
- **Storage:** 8GB Micro SD

Layer 2 Features

- **Switching Mode:** Store-and-Forward
- **Spanning Tree:**
 - 802.1w
 - 802.1s
 - Auto Edge
- **VLAN :**
 - IEEE 802.1Q Tagged Base
 - Port-Based
 - QinQ (802.1ad)
- **Storm Control:**
 - Broadcast
 - Unknown multicast
 - DLF (Unknown unicast)
- **IGMP Snooping:**
 - v1/v2/v3
 - v1/v2 Querier
 - Immediate Leave
- **Link Aggregation:**
 - 802.3ad with LACP
 - Static Trunk
 - Unicast/Multicast Traffic Balance over Trunking Port
 - LACP Fallback
- **Link state**
- **Port backup**
- **Error-Disable Recovery**

QoS Features

- **Scheduling for priority queue:** WRR, Strict, Hybrid
- **COS:** 802.1p, IP TOS precedence, DSCP
- **DiffServ**
- **iSCSI optimization**

Security Features

- **static and dynamic port security (MAC-based)**
- **802.1x:**
 - Port-based

- MAC-based
- Auto VLAN assignment
- Guest VLAN
- Unauthenticated VLAN
- **Access Control List:** L2/L3/L4
- **IPv6 ACL:** L3/L4
- **RADIUS:** Authentication, Accounting
- **TACACS+:** Authentication
- **SSH 1.5/V2.0**
- **User name and password:**
 - Local Authentication
 - Remote Authentication via RADIUS/TACACS+
 - AAA
- **Management IP filtering:**
 - SNMP
 - Telnet
 - SSH
- **IP Source Guard**
- **Dynamic ARP inspection (DAI)**
- **DHCP snooping**
- **Control Plane Policing / CoPP**
- **Service Prohibit Access**

Layer 3 Features

- **IP Multinetting/CIDR**
- **/31 subnets**
- **Proxy ARP**
- **Static route:** IPv4 , IPv6
- **OSPF**
- **ECMP**
- **BGP4**
- **IGMP v1/v2/v3**
- **PIM-DM/-SM**
- **VRRP**
- **Policy-based routing**
- **BFD**
- **VRF Lite**

IPv6 L3 Features

- **OSPFv3**
- **MLD v1/v2**
- **PIM-DM6/-SM6**

Data Center Features

- **Enhanced Transmission Selection (802.1Qaz)**
- **Priority-based Flow Control (802.1Qbb)**
- **DCBX:** DCBX for ETS, DCBX for PFC
- **FCoE Initiation Protocol (FIP) snooping**

SDN

- **OpEN API:** RESTful API

Management Features

- **Industrial command-line interface**
- **CLI filtering**
- **Telnet/SSH**
- **Software download/upload:** TFTP, FTP, SCP, SFTP
- **Configuration download/upload:** TFTP, FTP, SCP, SFTP
- **Dual Image**
- **SNMP v1/v2c/v3:** Yes (read only)
- **SNMP inform**
- **RMON 1, 2, 3, & 9:** Yes (read only)
- **BOOTP:** client/relay
- **DHCP client**
- **DHCP relay**
- **EVENT/Error log:** Local Flash
- **DNS client**
- **DNS relay**
- **Remote PING**
- **Traceroute**
- **SNTPv4**
- **LLDP:**
 - 802.1ab
 - 802.MED
 - Potential error detection
- **UDLD**
- **Port mirroring:** SPAN, RSPAN
- **sFlow v5**
- **Email alerting:** Yes (SMTP)
- **Auto Install**

IPv6 Management

- **IPv4/IPv6 Dual Protocol Stack**
- **ICMPv6**
- **ICMPv6 Redirect**
- **IPv6 Neighbor Discovery**
- **Stateless Autoconfiguration**
- **Manual Configuration**
- **DHCPv6:** Yes (client)
- **SNMP over IPv6**
- **SSH over IPv6**
- **IPv6 Telnet Support**
- **IPv6 DNS Resolver**
- **IPv6 RADIUS Support**
- **IPv6 TACACS+ Support**
- **IPv6 Syslog Support**
- **IPv6 SNTP Support**
- **IPv6 TFTP Support**

High Availability

- **Redundant power supply:** 1+1
- **Hot-swappable fan tray:** N+1
- **Multi-chassis LAG**

Virtualization Features

- **VXLAN**

Mechanical

- **Dimension (HxWxD):** 44x435x483mm
- **Weight:** 9.33kg/20.55lbs (NET)

Environmental Specifications

- **Operating temperature:** 0~45°C
- **Operating humidity:** 90% maximum relative humidity

Electrical

- **Power requirement:** 100~240VAC, 50/60Hz
- **Power consumption:** 200 watts (L2 line rate; 40G-SR optics, 100% fan duty)

Safety

- **UL, cUL, CB, CCC**

EMC

- **CE, FCC, VCCI, RCM, CCC**

RoHS

- **Reduction of Hazardous Substances (RoHS) 6**

Supported Optics and Cables

- **DAC cable (QSFP+):** 1m, 3m, and 5m
- **DAC cable (QSFP+, fan-out):** 1m, 3m, and 5m
- **AOC cable (QSFP+, 850nm, MMF):** 7m, 10m, and 20m
- **40G optic (QSFP+, MPO, 850nm, MMF):** 10GBASE-SR4
- **40G optic (QSFP+, LC, 1310nm, SMF):** 10GBASE-LR4

Order Information

- **T5032-LY6 (1LY6BZZ0STF) (F-2-B, AC, P2020)**
- **T5032-LY6 (1LY6BZZ0STG) (B-2-F, AC, P2020)**
- **PSU - Blue (1HY9ZZZ016B) (F-2-B, AC, 470W)**
- **PSU - Green (1HY9ZZZ016C) (B-2-F, AC, 470W)**
- **FAN Module (1HY9ZZZ022X) (F-2-B, Red)**
- **FAN Module (1HY9ZZZ022Y) (B-2-F, Blue)**

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their respective holders. Copyright © 2014-2017 Quanta Computer Inc. All rights reserved.

